

Setup Location from Tablet Command - Inform CAD

1

1. If necessary, update the Tablet Command Interface
2. Enable Real Time Location.
3. Restart the Interface.

2

1. Ensure that in the CAD Vehicle Manager AVL Enabled is checked for each vehicle that will be deriving its location from Tablet Command. In this example the vehicle is 4701

3

Vehicle ID	Radio Name	Map Status	Station	Last Updated	Map Action	Location To CAD
M5	M5	Visible	STA 5 code: 5	in a few seconds	Hide Location	Enable To CAD
E11	E11	Visible	STA 11 code: 11	in a few seconds	Hide Location	Enable To CAD
SND112	SND112	Visible	SND STA 12 code: SND12	in a few seconds	Hide Location	Enable To CAD
M3	M3	Visible	STA 3 code: 3	a few seconds ago	Hide Location	Enable To CAD
M439	M439	Visible	STA 9 code: 9	a few seconds ago	Hide Location	Enable To CAD
E39	E39	Visible	STA 39 code: 39	a few seconds ago	Hide Location	Enable To CAD
T34	T34	Visible	STA 34 code: NC34	a minute ago	Hide Location	Enable To CAD
E4	E4	Visible	STA 4 code: 4	a minute ago	Hide Location	Enable To CAD
M2	M2	Visible	STA 2 code: 2	2 minutes ago	Hide Location	Enable To CAD
E2	E2	Visible	STA 2 code: 2	2 minutes ago	Hide Location	Enable To CAD

1. Under Admin Features > CAD STATUS > CAD Vehicles click "Enable To CAD"

4

1. Under Admin Features > Users > User Details there will be a message indicating the the vehicle is enabled for location to CAD, and the ability to hide the iPad location is disabled